

Series **CR(CV)–ARD**


Clean Series Round Cylinder

Bore Size : $\varnothing 50$, $\varnothing 63$



- CYLINDER IN LOW PARTICLE GENERATION FOR CLEAN ROOM.
- PISTON ROD IS MADE IN THE MATERIAL QUALITY OF STAINLESS STEEL TO ENHANCE RESISTANCE AGAINST MOISTURE AND OTHER CHEMICALS.
- EXCLUSIVE GREASE USE, DUST GENERATION IS MINIMIZED WHEN CYLINDER IS ACTING.

How to Order

CR(CV) — **ARD** **B** **A** **50** — **150** — **W5** 

1 2 3 4 5 6 7 8

1 Clean Series

CR : relief port type
CV : vacuum suction type

2 Round Cylinder

Magnet, bumper, non-lube types are standard

3 Mounting

B : basic type
※ For foot and flange type, please contact us.

4 Cushion(rubber cushion is provided.)

Blank : rubber cushion
A : air cushion

5 Bore Size

50 : 50mm
63 : 63mm

6 Stroke(mm)

Stroke : 20–300
※ For long stroke, please contact us for confirmation.

7 Auto Switch

– Reed switch
– Band attached type(grommet)
: W5
※ The length of lead wire is 0.5m (standard).
For 3m, L is added to the end of part number.
ex) W5L

8 Number of Auto Switches

Blank : 2 pcs
S : 1 pc
N : N pcs